

CLAIMS

What is claimed is:

1. A prioritized address decoder comprising:
a first comparator to compare a destination device address of data with a first address range associated with a first device; and
a second comparator coupled to the first comparator to compare the destination device address with a second address range associated with a second device, wherein the data is sent to the second device in response to a first output of the first comparator and a second output of the second comparator.
2. The prioritized address decoder of claim 1, wherein the first comparator disables the second comparator when the destination device address is within the first address range.
3. The prioritized address decoder of claim 1, further comprising a third comparator coupled to the first and the second comparators to compare the destination device address with a third address range associated with a third device, wherein the data is sent to the third device in response to a third output of the third comparator, the second output of the second comparator, and the first output of the first comparator.

4. The prioritized address decoder of claim 3, wherein the third comparator is disabled when the address is within either the first address range or the second address range.
5. The prioritized address decoder of claim 1, wherein the first address range is associated with a first device of a computer system, secured data in the computer system is authorized to be sent to the first device.
6. The prioritized address decoder of claim 5, wherein the second address range is associated with a second device of the computer system, the secured data is not authorized to be sent to the second device.
7. A method to route data in a computer system comprising:
 - determining whether a destination address of the data is associated with one of a plurality of trusted agents in the computer system;
 - sending the data to one trusted agent of the plurality of trusted agents if the destination address is associated with the one trusted agent; and
 - blocking the data from a plurality of non-trusted agents if the destination address is associated with the one trusted agent.
8. The method of claim 7, further comprising determining whether the destination address is associated with one of a plurality of non-trusted agents if the destination address is associated with none of the plurality of trusted agents.

9. The method of claim 7, wherein the data is secured data in the computer system.
10. The method of claim 9, wherein determining whether the destination address of the data is associated with any one of the plurality of trusted agents comprises comparing the destination address with a plurality of configuration bits corresponding to each of the plurality of trusted agents.
11. The method of claim 10, wherein the plurality of configuration bits are associated with an address range.
12. A computer system comprising:
- a dynamic random access memory (DRAM);
 - a memory controller, coupled to the DRAM, the memory controller comprising a prioritized address decoder, the prioritized address decoder including
 - a first comparator to compare a destination device address of data with a first address range associated with a first device; and
 - a second comparator coupled to the first comparator to compare the destination device address with a second address range associated with a second device,wherein the data is sent to the second device in response to a first output of the first comparator and a second output of the second comparator.

13. The computer system of claim 12, wherein the first comparator disables the second comparator when the destination device address is within the first address range.
14. The computer system of claim 12, wherein the prioritized address decoder further comprises:
- a third comparator coupled to the first and the second comparators to compare the destination device address with a third address range associated with a third device, wherein the data is sent to the third device in response to a third output of the third comparator, the second output of the second comparator, and the first output of the first comparator.
15. The computer system of claim 12, wherein the first address range is associated with a trusted agent.
16. The computer system of claim 15, further comprising a processor coupled to the memory controller, wherein the trusted agent is the processor.
17. The computer system of claim 12, wherein the second address range is associated with a non-trusted agent.
18. The computer system of claim 12, wherein the memory controller further comprises a plurality of configuration registers storing information on the first and the second address ranges.

19. The computer system of claim 18, wherein the information is stored in the plurality of configuration registers during configuration.

20. The computer system of claim 18, wherein the plurality of configuration registers are locked during a trusted mode.